

**QMFZ2.E220856 – QMFZ8.E220856**  
**Plastic – Component**  
**Plastics Certified for Canada – Component**



<b>COLOR TECH SRL</b>	File Number E220856
VIA DELL'INDUSTRIA, 6 – 31020 SAN POLO DI PIAVE (TV)	

Mtl Dsg	Color	Min. Thk mm	Flame Class	H W I	H A I	H V A	R T I			H	D	
							Elec	Mech		V	4	C
							Imp	Str	T	9	T	
									R	5	I	
<b>Acrylonitrile Butadiene Styrene (ABS), furnished as pellets.</b>												
<a href="#">ABS Teclan 100MT-F(a)</a>	ALL	1.5	HB	-	-	-	60	60	60	-	-	-
<a href="#">TECLAN 110 FE</a>	ALL	1.6-2.99	HB	-	-	-	60	60	60	-	-	-
	WT, RD, BK	1.6	HB	-	-	-	60	60	60	-	-	-
		3.0	HB	-	-	-	60	60	60	-	-	-
<a href="#">TECLAN 110 FVO</a>	ALL	1.5	V-0	-	-	-	60	60	60	-	-	-
<a href="#">TECLAN 110 UTFR</a>	ALL	1.5	V-0	2	-	-	60	60	60	-	-	-
	ALL	3.0	V-0;5VA	1	-	-	60	60	60	-	-	-
<b>Acrylonitrile Butadiene Styrene (ABS).</b>												
<a href="#">TECLAN 110 SF</a>	ALL	1.6	HB	-	-	-	60	60	60	-	-	-
	ALL	3.0	HB	-	-	-	60	60	60	-	-	-
<b>Acrylonitrile Butadiene Styrene/Polycarbonate (ABS/PC), furnished as pellets.</b>												
<a href="#">TEC BLEND E65 FR</a>	ALL	1.5	V-0	-	-	-	60	60	60	-	-	-
<b>Polycarbonate (PC)</b>												
<a href="#">PC TECLUX FR15 AF(b)(c)</a>												
	ALL	1.6	V-2	2	1	3	80	80	80	2	-	-
		3.0	V-0	2	0	3	80	80	80			

- (a) – represents a four digit number color.
- (b) – represents an alphanumeric code indicating color.
- (c) – Vicat softening temperature of 146 C degree at 3.0 mm

Marking: Company name and material designation, generic polymer identification, color number where appropriate and batch or lot number or date of manufacture on container, wrapper or molded on finished part.